

NFM630R

13GAUGE



ANSI/ISEA 105



EN388



4X43F



STANDARD 100
SHO20 126980
TESTEX



ATTRIBUTES:

- 13g Black and Grey Engineered Cut F Liner,
- Black Smooth Nitrile Full Coating with Black HCT® Microfoam Nitrile Palm Coating

APPLICATIONS:

- Cutting small parts
- Sheet metal work
- Delicate and precise operations
- Automotive

PACKAGING:

GLOVE SIZE	6	7	8	9	10	11
CUFF COLOR	Purple	Red	Yellow	Brown	Black	Blue
PER CASE	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

SUSTAINABILITY EFFORTS:

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

CATEGORY:

BASETEK®

CLEANING / MAINTENANCE:

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.