

# HDPKNF

**13GAUGE**

**ANSI/ISEA 105**

**EN388**

**4X43C**

**STANDARD 100**  
SH020 126980  
TESTEX







**ATTRIBUTES:**

- 13g Salt & Pepper HDPE Cut C Liner
- Black Foam Nitrile Knuckle Coating

**APPLICATIONS:**

- Handling/assembling small oily parts
- General assembly
- Machining
- Micro-engineering
- Automotive components

**PACKAGING:**

<b>GLOVE SIZE</b>	6	7	8	9	10	11
<b>CUFF COLOR</b>	 Purple	 Red	 Yellow	 Brown	 Black	 Blue
<b>PER CASE</b>	6DZ	6DZ	6DZ	6DZ	6DZ	6DZ

**SUSTAINABILITY EFFORTS:**

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

**CATEGORY:**
**BASETEK®**
**CLEANING / MAINTENANCE:**

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.