


**EN388**

**3131X**

**STANDARD 100**  
SHO20 126980  
TESTEX

**ATTRIBUTES:**

- 13g White Nylon Liner
- Grey Smooth Nitrile Knuckle Coating

**APPLICATIONS:**

- Handling/assembling small oily parts
- General assembly
- Machining
- Micro-engineering
- Automotive components

**PACKAGING:**

<b>GLOVE SIZE</b>	6	7	8	9	10	11
<b>CUFF COLOR</b>	Purple	Red	Yellow	Brown	Black	Blue
<b>PER CASE</b>	12DZ	12DZ	12DZ	12DZ	12DZ	12DZ

**SUSTAINABILITY EFFORTS:**

QS Safety has long been a pioneer in responsible and environmentally friendly manufacturing practices. Over the past 30 years, we have remained committed to doing our part to produce protective gloves in the most ethical and environmentally friendly way possible.

**CATEGORY:**
**DUTY**
**CLEANING / MAINTENANCE:**

Recommended washing temperature is between 40°C and 60°C (104°F – 140°F). Use a standard laundry detergent or cleaning product. Do not dry clean. The drying process may cause felting on the fabric surface. Drying temperatures should not exceed 70°C (158°F). Important: Washing and use may decrease the glove's effectiveness over time.